

# Technical data sheet

## Clamp clip 2056 W-foot, 1-fold, plastic pressure sleeve, Al

Item number: 1187944



Clamp clip with W-foot, plastic pressure sleeve made of polypropylene. For vertical and horizontal mounting of 1 single cable on angle irons < 40 mm. With 1-start screw thread on pressure sleeve, universal hexagonal screw head WAF10, with slot and cross recess. Suitable for assembly indoors and outdoors. We recommend the use of a counter-sleeve.



**Alu** Aluminium

### Master data

|                                   |                         |
|-----------------------------------|-------------------------|
| Item number                       | 1187944                 |
| Type                              | BS-W1-K-52 ALU          |
| Description 1                     | Clamp clip 2056         |
| Manufacturer                      | OBO                     |
| Dimension                         | 46-52mm                 |
| Material                          | Aluminium               |
| Smallest sales unit               | 50                      |
| Unit of quantity                  | Piece                   |
| Weight                            | 4.8 kg                  |
| Weight unit                       | kg/100 pc.              |
| CO Footprint (GWP) Cradle-to-Gate | 0,6026 kg COe / 1 Piece |


# Technical data sheet

Clamp clip 2056 W-foot, 1-fold, plastic pressure sleeve, Al

Item number: 1187944



## Dimensions



|                  |        |
|------------------|--------|
| Length           | 25 mm  |
| Width            | 57 mm  |
| Height           | 122 mm |
| Plate thickness  | 2 mm   |
| Dimension A      | 25 mm  |
| Dimension B      | 57 mm  |
| Dimension C      | 40 mm  |
| Dimension G (mm) | M8     |
| Dimension H      | 122 mm |
| Dimension L      | 45 mm  |
| Dimension t      | 2 mm   |

## Technical data

|                               |               |
|-------------------------------|---------------|
| Number of cables/pipes        | 1             |
| For pipe diameter, max.       | 52 mm         |
| For pipe diameter, min.       | 46 mm         |
| Thread                        | M8            |
| Halogen-free                  | yes           |
| Length of external dimensions | 40 mm         |
| Max. Tightening torque        | 2 Nm          |
| With plastic trough           | yes           |
| Mounting type                 | Angle profile |
| Slot width                    | 10 mm         |
| Clamping range D, max.        | 52 mm         |
| Clamping range D, min.        | 46 mm         |
| Surface addition              | Untreated     |
| Material addition             | Aluminium     |
| With counter-trough           | no            |
| Material of trough            | Plastic       |
| Material quality of trough    | Polypropylene |