Technical data sheet

Underfloor duct, 2 pieces, 2-compartment, duct height 38 mm

Item number: 7400258



Underfloor duct (2 piece) for routing cables in screed-covered underfloor systems, according to EN 50085-2-2. Removable and continuously lockable trunking cover. With separating retainers in the trunking base. Maximum load-bearing capacity to 1.5 kN.

The profiled side walls offer a locking mechanism to lock the duct cover onto the duct base. The stiffening beads in the duct cover serve to create stability.





St

Steel

FS

Strip galvanized

Master data

Item number	7400258	
Туре	S2 19038-2	
Description 1	Underfloor duct, 2-part	
Description 2	2 compartments	
Manufacturer	OBO	
Dimension	2000x190x38	
Material	Steel	
Surface	Strip galvanized	
Surface standard	DIN EN 10346	
Smallest sales unit	2	
Unit of quantity	Metre	
Weight	321.425 kg	
Weight unit	kg/100 m	
CO2 Footprint (GWP) Cradle-to- Gate	7,0935 kg CO2e / 1 Meter	

Technical data sheet

Underfloor duct, 2 pieces, 2-compartment, duct height





Dimensions		
a b	Length	2,000 mm
7	Width	190 mm
	Height	38 mm
	Dimension a	80 mm
	Dimension b	110 mm
	Dimension h	38 mm

St.
loor
es
creed-covered
0
90 mm
8 mm
369 mm²
es
639 mm²
730 mm²
1,500 N
10 e 0 9 8 3 e 6 7