### **Technical data sheet**

## Underfloor duct, 2 pieces, 2-compartment, duct height 28 mm

**Item number: 7400265** 





Underfloor duct (2 piece) for routing cables in screed-covered underfloor systems, according to EN 50085-2-2. Removable and continuously lockable trunking cover. With separating retainers in the trunking base. Maximum load-bearing capacity to  $1.5\ kN$ .

The profiled side walls offer a locking mechanism to lock the duct cover onto the duct base. The stiffening beads in the duct cover serve to create stability.



St

Steel

FS

Strip galvanized

#### Master data

Item number	7400265
Туре	S2 25028-2
Description 1	Underfloor duct, 2-part
Description 2	2 compartments
Manufacturer	OBO
Dimension	2000x250x28
Material	Steel
Surface	Strip galvanized
Surface standard	DIN EN 10346
Smallest sales unit	2
Unit of quantity	Metre
Weight	369.106 kg
Weight unit	kg/100 m
CO2 Footprint (GWP) Cradle-to- Gate	8,1488 kg CO2e / 1 Meter

### **Technical data sheet**

# Underfloor duct, 2 pieces, 2-compartment, duct height 28 mm





Dimensions		
a b	Length	2,000 mm
	Width	250 mm
	Height	28 mm
	Dimension a	110 mm
	Dimension b	140 mm
	Dimension h	28 mm

Number of fixed partitions	1
Number of compartments	2 St.
Mounting system fastening type	Floor
Floor plate	yes
Application area	Screed-covered
Decouplable	no
Trunking width, min.	250 mm
Duct height, min.	28 mm
Usable cross-section	6184 mm²
Removable cover	yes
Cross-section, draw a	2701 mm²
Cross-section, draw b	3483 mm²
Vertical load, large area	to 1,500 N
	Number of compartments Mounting system fastening type Floor plate Application area Decouplable Trunking width, min. Duct height, min. Usable cross-section Removable cover Cross-section, draw a Cross-section, draw b