## **Technical data sheet**

# Underfloor duct, 2 pieces, 3-compartment, duct height 48 mm

**Item number: 7400281** 





Underfloor trunking (2 piece) for routing cables in screed-covered underfloor systems, according to EN 50085-2-2. Removable and continuously lockable trunking cover. With separating retainers in the trunking base. Maximum load-bearing capacity to 1.5 kN.

The profiled side walls offer a locking mechanism to lock the duct cover onto the duct base. The stiffening beads in the duct cover serve to create stability.



St

Steel

FS

Strip galvanized

#### Master data

Item number	7400281
Туре	S3 25048-2
Description 1	Underfloor duct, 2-part
Description 2	3 compartments
Manufacturer	OBO
Dimension	2000x250x48
Material	Steel
Surface	Strip galvanized
Surface standard	DIN EN 10346
Smallest sales unit	2
Unit of quantity	Metre
Weight	453.8 kg
Weight unit	kg/100 m
CO2 Footprint (GWP) Cradle-to- Gate	10,0773 kg CO2e / 1 Meter

## **Technical data sheet**

### Underfloor duct, 2 pieces, 3-compartment, duct height 48 mm





Dimensions		
a b a	Length	2,000 mm
}	Width	250 mm
	Height	48 mm
	Dimension a	90 mm
	Dimension b	70 mm
	Dimension h	48 mm

Technical data		
	Number of fixed partitions	2
	Number of compartments	3 St.
	Mounting system fastening type	Floor
	Floor plate	yes
	Application area	Screed-covered
	Decouplable	no
	Trunking width, min.	250 mm
	Duct height, min.	48 mm
	Usable cross-section	10892 mm²
	Removable cover	yes
	Cross-section, draw a	3854 mm²
	Cross-section, draw b	3184 mm²
	Vertical load, large area	to 1,500 N