Technical data sheet

Underfloor duct, 2 pieces, 3-compartment, duct height 28 mm

Item number: 7400287





Underfloor duct (2 piece) for routing cables in screed-covered underfloor systems, according to EN 50085-2-2. Removable and continuously lockable trunking cover. With separating retainers in the trunking base. Maximum load-bearing capacity to 1.5 kN.

The profiled side walls offer a locking mechanism to lock the duct cover onto the duct base. The stiffening beads in the duct cover serve to create stability.



St

Steel

FS

Strip galvanized

Master data

Item number	7400287
Туре	S3 35028-2
Description 1	Underfloor duct, 2-part
Description 2	3 compartments
Manufacturer	OBO
Dimension	2000x350x28
Material	Steel
Surface	Strip galvanized
Surface standard	DIN EN 10346
Smallest sales unit	2
Unit of quantity	Metre
Weight	503.717 kg
Weight unit	kg/100 m
CO2 Footprint (GWP) Cradle-to- Gate	11,244 kg CO2e / 1 Meter

Technical data sheet

Underfloor duct, 2 pieces, 3-compartment, duct height 28 mm





Dimensions		
a b a	Length	2,000 mm
	Width	350 mm
	Height	28 mm
•	Dimension a	120 mm
	Dimension b	110 mm
	Dimension h	28 mm

	Diffictional	20 11111
Technical data		
	Number of fixed partitions	2
	Number of compartments	3 St.
	Mounting system fastening type	Floor
	Floor plate	yes
	Application area	Screed-covered
	Decouplable	no
	Trunking width, min.	350 mm
	Duct height, min.	28 mm
	Usable cross-section	8722 mm²
	Removable cover	yes
	Cross-section, draw a	2944 mm²
	Cross-section, draw b	2834 mm²
	Vertical load, large area	to 1,500 N