Technical data sheet

Underfloor duct, 2 pieces, 3-compartment, duct height 58 mm

Item number: 7400293





Underfloor trunking (2 piece) for routing cables in screed-covered underfloor systems, according to EN 50085-2-2. Removable and continuously lockable trunking cover. With separating retainers in the trunking base. Maximum load-bearing capacity to 1.5 kN. Only compatible with the UZD250-4/350-4

The profiled side walls offer a locking mechanism to lock the duct cover onto the duct base. The stiffening beads in the duct cover serve to create stability.



St

Steel

FS

Strip galvanized

Master data

| Item number | 7400293 | |
|--|---------------------------|--|
| Туре | S3 35058-2 | |
| Description 1 | Underfloor duct, 2-part | |
| Description 2 | 3 compartments | |
| Manufacturer | OBO | |
| Dimension | 2000x350x58 | |
| Material | Steel | |
| Surface | Strip galvanized | |
| Surface standard | DIN EN 10346 | |
| Smallest sales unit | 2 | |
| Unit of quantity | Metre | |
| Weight | 422.969 kg | |
| Weight unit | kg/100 m | |
| CO2 Footprint (GWP) Cradle-to- Gate | 13,0595 kg CO2e / 1 Meter | |

Technical data sheet

Underfloor duct, 2 pieces, 3-compartment, duct height





| Dimensions | | |
|------------|-------------|----------|
| a b a | Length | 2,000 mm |
| | Width | 350 mm |
| | Height | 58 mm |
| | Dimension a | 120 mm |
| | Dimension b | 110 mm |
| | Dimension h | 58 mm |

| Technical data | | |
|----------------|--------------------------------|----------------|
| | Number of fixed partitions | 2 |
| | Number of compartments | 3 St. |
| | Mounting system fastening type | Floor |
| | Floor plate | yes |
| | Application area | Screed-covered |
| | Decouplable | no |
| | Trunking width, min. | 350 mm |
| | Duct height, min. | 58 mm |
| | Usable cross-section | 18794 mm² |
| | Removable cover | yes |
| | Cross-section, draw a | 6341 mm² |
| | Cross-section, draw b | 6112 mm² |
| | Vertical load, large area | to 1,500 N |