


Technical data sheet

Short support for PV module mounting, flat roof

Item number: 5901650



Short support to mount photovoltaic modules on flat roofs in combination with the TP 45/4700 support profile and KLU universal clamp. Slope angle 15°. Lockable fastening on support profile.



St

Steel

DD

Strip galvanised zinc/aluminium, Double Dip

Master data

Item number	5901650
Type	STK DD
Description 1	Short support
Description 2	for flat roof system
Manufacturer	OBO
Dimension	86x166x107
Colour	zinc
Material	Steel
Surface	Strip galvanised zinc/aluminium, Double Dip
Surface standard	DIN EN 10346
Smallest sales unit	8
Unit of quantity	Piece
Weight	93 kg
Weight unit	kg/100 pc.
CO2 Footprint (GWP) Cradle-to-Gate	2,9964 kg CO2e / 1 Piece


Technical data sheet

Short support for PV module mounting, flat roof

Item number: 5901650



Dimensions



Length	163 mm
Width	87 mm
Height	116 mm

Technical data

Angle of inclination, max.	15 °
Angle of inclination, min.	15 °
Depth	0 mm
Adjustable	yes
Photovoltaic connection and fastening element version	Other
Mounting type photovoltaic mounting systems	Flat roof
Torsion spring stiffness (k.rot.y)	0
Torsion spring stiffness (k.rot.z)	0