

Technical data sheet

Coaxial protection device for BNC connection: male/female

Item number: 5093252



Coaxial data cable protection devices

- Basic protection
- High pulsed current carrying capacity 2 x 2.5 kA (10/350 µs)
- Simple installation (adapter plug), m = plug/f = female connector
- Various plug combinations
- With BNC connector
- Optimised transmission behaviour
- Including OBO M25 Quick clip for simple installation



Master data		
Item number	5093252	
Type	DS-BNC M/W	
Description 1	Protection device	
Description 2	for high-frequency cables	
Manufacturer	OBO	
Dimension	130V	
Smallest sales unit	1	
Unit of quantity	Units	
Weight	8,64 kg	
Weight unit	kg/100 pairs	
CO2 Footprint (GWP) Cradle-to-Gate	0,0435 kg CO2e / 1 Piece	

Dimensions	

Technical data sheet

Coaxial protection device for BNC connection: male/female

Item number: 5093252



Technical specifications

Arrestor monitoring	no
Number of poles	1
Insertion loss	≤0,95 dB
Explosion-tested version	no
Telecommunications contact	no
Total discharge current (10/350)	D1: 5 kA
Total discharge current (8/20)	10 kA
Cut-off frequency	2200 MHz
Maximum continuous voltage AC	130 V
Maximum continuous voltage DC	185 V
Lightning impulse current	2,5 kA
Insulation resistance	>1 GΩ
Capacity (wire-wire)	<40 pF
Capacity (wire-earth)	<20 pF
Kategorie	Type 1+2 / D1+C2
Lightning protection zone LPZ	0→2
Mounting type	Connector/cable adapter
Nominal load current AC	7 A
Nominal load current DC	10 A
Testing standard	IEC 61643-21
ROHS-conformant	yes
Return loss	≥14 dB
Shielding connection available	yes
Shield connection	Direct
Protection rating	IP40
Protection level	<800 V
Protection level wire-wire	<800 V
Protection level wire-earth	<800 V
Signalling on device	None
SPD to IEC 61643-21	Class I+II / D1+C2
Plug-in system	BNC
Impulse durability wire-wire	C2: 10 kV / 5 kA (8/20μs)
Impulse durability wire-earth	C2: 10 kV / 5 kA (8/20μs)
Permitted temperature range, max.	80 °C
Permitted temperature range, min.	-40 °C
Wave resistance	50 Ω